

3 PHASE OUTPUTS					
GENERATOR SET MODEL	RATING	50HZ		60HZ	
		380-415 V, 1500 rpm		480 V, 1800 rpm	
		KVA	KW	KVA	KW
PM-1250	STAND-BY	1250	1000	-	-
	PRIME	1125	900	-	-



POWERED BY:  

* Ratings at 0.8 pf - Generator designed to operate in ambient temperatures up to 52 °C
* Generating Set photo is for reference only.

ALTERNATOR DATA

Make	Leroy Somer
Model	LSA 50.2 M6
No. of bearings	1
Insulation Class	H
Total Harmonic Content	<5 %
Wires	6
Ingress Protection	IP23
Excitation System	SHUNT
Winding Pitch	2/3 (n° 6S)
AVR Model	R150
Overspeed	2250 mn ⁻¹
Voltage Regulation	±1%

CONTROL PANEL

Make	Deepsea
Model	DSE7320
DSE7320 is an Auto Mains (Utility) Failure Control Module. It is operated via the START, STOP, AUTO, and MANUAL soft touch membrane buttons on the front panel. DSE7320 can be controlled remotely using either GDM Modem, Ethernet via DSE860/865 or via RS485.	
PROTECTION:	
-Fail to start	
-Low oil pressure	
-High engine temperature	
-U/O Voltage shutdown	
-U/O Frequency shutdown	
-Underspeed, Overspeed	
-Loss of speed engine detection	
-High/Low battery voltage	
-kW overload	
-Unbalanced load	
-Low fuel alarm (if fitted)	
-Battery charger failure (if fitted)	

ENGINE / TECHNICAL DATA

Engine Make	Perkins	
Engine Model	4008-30TAG3	
Governing Type	ISO 3046-4 A1	
Cylinder Arrangement	Vertical in line	
Number of Cylinders	8	
Bore and Stroke	160 x 190	
Displacement/Cubic Capacity liters	30.6	
Induction System	Turbocharged and air to air charge cooled	
Cycle	4 Stroke	
Combustion System	Direct Injection	
Compression Ratio	13.6:1	
Rotation	Anti-clockwise (viewed from flywheel)	
Cooling System	Water-cooled	
Frequency and Engine Speed	50Hz & 1500rpm	
	Prime	Standby
Gross Engine Power kW (hp)	947 (1270)	1055 (1408)
FUEL CONSUMPTION (L/hr)		
	50%	120
	75%	188
	100%	244
		269
Total Lubrication System Capacity [liters]	165.6	165.6
Total Coolant Capacity (inc. radiator) [ltrs]	162	162
Boost Pressure Ratio	3.86	4.20
Exhaust Temperature °C	473	482
Radiator Cooling Air Flow (Min): m ³ /sec	19	19.6
Combustion Air Flow: m ³ /sec	84	96
Exhaust Gas Flow: m ³ /sec	203	240
Fuel Tank Capacity	N/A	N/A

Dimension and Weight

DIMENSION	OPEN	SILENT
Length (L)	4300 mm	12000 mm
Width (W)	1740 mm	2320 mm
Height (H)	2150 mm	2900 mm
Net Weight	6360 kg	4000 kg*
	*container without genset	(40' ISO)

RATING DEFINITIONS:

Prime Power - These ratings are applicable for supplying continuous power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Power - These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these rating. When used at standby Rating the alternator will be peak continuous rated (according to ISO3046)

STANDARD SPECIFICATIONS

1. ENGINE

Perkins heavy duty diesel engine.

1.1 GOVERNOR

Electronic, compliance with ISO8528, Class G2.

2. COOLING RADIATOR

Radiator and cooling fan complete with protection guards, designed to cool the engine in ambient temperatures up to 52° C. The radiator is mounted on the base frame to avoid vibrations coming from the engine.

3. FILTRATION SYSTEM

Cartridge type air filter with security element. Cartridge fuel filter and full lube oil filter. All filters have replaceable elements.

4. EXHAUST SYSTEM

Heavy-duty industrial silencer.

5. ELECTRICAL SYSTEM

12 Volt system with battery charging alternator, Starter motor, High capacity maintenance free lead acid battery, battery rack mounted on the generating set base frame, and heavy duty interconnecting cables with terminations.

6. ALTERNATOR

Screen protected and drip-proof, self-exciting, self-regulating brush-less alternator. Four poles, STAR winding connection, suitable for tropical, humid and saline climates. H class insulation.

7. AUTOMATIC VOLTAGE REGULATOR (AVR)

Static electronic design voltage regulator. Steady voltage precision within + 1 % from no load to full load including cold and hot variations, at any Power factor between 0.8 and unity.

8. MOTOR STARTING

An overload capacity equivalent to between 160% to 300% (depending on alternator frame size) of full load impedance at zero power factor can be sustained for 10 seconds.

9. MOUNTING ARRANGEMENT

9.1 BASE FRAME

The complete generating set is mounted on heavy duty steel fabricated base frame Which is anti rust coated.

9.2 COUPLING

Engine and alternator are directly coupled by means of SAE flange so there is no possibility of misalignment after prolong use. The engine fly wheel is flexibly coupled to the alternator rotor.

9.3 ANTI VIBRATION MOUNTING PADS

Anti vibration pads are fitted between engine-alternator base frame ensuring complete vibration isolation of rotating assemblies.

10. FUEL SYSTEM

Metal Fuel tank of 180 litres capacity. The Fuel tank is easy to clean and is equipped with visual fuel level indicator.

11. DOCUMENTATION

A full set of operation and maintenance manual are provided.

12. FACTORY TESTS

Generating set is subject to a strict load test before delivery. A test certificate can be provided as optional.

13. QUALITY STANDARDS

Generating set meets the following standards ISO 8528, IEC 34.1, CEI 2.3, VDE 0530, BS 4999-5000, NF51-100. Perkins is fully accredited ISO 9001 company.

14. WARRANTY

Generating set is guaranteed for a period of 12 months from date of commissioning or 18 months from date of shipment which ever occurs earlier. (check warranty statement for more details, as it may vary for different countries)

In line with our policy of continuous product development, we reserve right to change specification without notice

AVAILABLE OPTIONS & ACCESSORIES

We offer a range of optional features and accessories to tailor our generating sets to meet your needs.

OPTIONS

- Generator Set control and synchronizing panels
- Additional Protection alarms and shutdowns
- Water fuel separator
- Water jacket heater
- Battery charger

ACCESSORIES

- Genuine spare parts
- Fuel Tanks
- Manual and Automatic Transfer Switches

STANDARD REFERENCE CONDITIONS

Output ratings are presented at 25°C air Inlet temperature, 1000 m bar and 30% relative humidity. Fuel consumption data at various loads, diesel fuel with a specific gravity of 0.85kG/L. De-ration may apply, please consult your dealer for specific site ratings.
Some of the specifications are not standard on all Genset Models.

Distributed and Serviced by:



T: +971 4 8833456
F: +971 4 8833458

Warehouse No RA08 XA-04
P. O. Box 17305 Jebel Ali, Dubai, UAE



www.adpower.ae
sales@adpower.ae

